



# SLA-2M2800D

2M Lens Module



## Key Features

- Compatible with PNM-7000VD

## Compatible Accessories (Optional)



PNM-7000VD

# SLA-2M2800D

## 2M Lens Module



### Specifications

| Video                       |  |
|-----------------------------|--|
| Imaging Device              | 1/2.8" 2MP CMOS  |
| Effective Pixels            | 1945(H)x1109(V)  |
| Min. Illumination           | Color: 0.055Lux(F2.0, 1/30sec)<br>B/W: 0.055Lux(F2.0, 1/30sec) |
| Lens                        |  |
| Focal Length (Zoom Ratio)   | 2.8mm fixed focal  |
| Max. Aperture Ratio         | F2.0   |
| Angular Field of View       | H:107.4°, V:62.2°, D:122.0°                                    |
| Focus Control               | Fixed  |
| Pan / Tilt / Rotate         |  |
| Pan / Tilt / Rotate Range   | -176°~+176° / 0°~50° / -90°~+90°                               |
| Mechanical                  |  |
| Color / Material            | Black / Plastic  |
| Product dimensions / weight | Ø35.5x27.9mm, 27g  |

## Compatible lenses



| Video                       | SLA-2M3600D  | SLA-2M2400D  | SLA-2M6000D  |
|-----------------------------|--|--|--|
| Imaging Device              | 1/2.8" 2MP CMOS  | 1/2.8" 2MP CMOS  | 1/2.8" 2MP CMOS  |
| Effective Pixels            | 1945(H)x1109(V)  | 1945(H)x1109(V)  | 1945(H)x1109(V)  |
| Min. Illumination           | Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec) | Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec) | Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec) |
| Lens                        | SLA-2M3600D  | SLA-2M2400D  | SLA-2M6000D  |
| Focal Length (Zoom Ratio)   | 3.6mm fixed focal  | 2.4mm fixed focal  | 6.0mm fixed focal  |
| Max. Aperture Ratio         | F2.0   | F2.0   | F2.0   |
| Angular Field of View       | H:94.8°, V:49.3°, D:114.3°                                   | H:135.4°, V:71.2°, D:161.6°                                  | H:50.4°, V:28.8°, D:58.1°                                    |
| Lens Type                   |  |  |  |
| Mount Type                  |  |  |  |
| Focus Control               | Fixed  | Fixed  | Fixed  |
| Pan / Tilt / Rotate         | SLA-2M3600D  | SLA-2M2400D  | SLA-2M6000D  |
| Pan / Tilt / Rotate Range   | -176°~+176° / 0°~54° / -90°~+90°                             | -176°~+176° / 0°~30° / -90°~+90°                             | -176°~+176° / 0°~65° / -90°~+90°                             |
| Operational                 | SLA-2M3600D  | SLA-2M2400D  | SLA-2M6000D  |
| Wide Dynamic Range          |  |  |  |
| Day & Night                 |  |  |  |
| Mechanical                  | SLA-2M3600D  | SLA-2M2400D  | SLA-2M6000D  |
| Color / Material            | Black / Plastic  | Black / Plastic  | Black / Plastic  |
| Product dimensions / weight | Ø35.5x27.9mm, 27g  | Ø35.5x27.9mm, 30g  | Ø35.5x27.9mm, 27g  |